

Laser Marking System

Videojet® 3340

The 3340 30-Watt laser offers a powerful combination of performance and flexibility delivering high quality marks on moderate to high speed lines.

High speed packaging operations that demand crisp, high quality codes can rely on the performance of the 3340. With virtually no font, code or graphic restrictions and line speeds up to 600m/min., the 3340 is an ideal solution for marking complex codes at high speeds in food, beverage, cosmetics, pharmaceutical and extrusion industries.

Through a diverse combination of marking heads, lenses and wavelength options, Videojet can deliver 24 spot size options to match a broad range of marking effects.



Uptime Advantage

- Maximum performance and extended laser source life expectancy up to 45,000 hours through optimized total power output
- Air-cooled laser source virtually eliminates maintenance intervals
- Line set-up wizard aids fast product changeovers, eliminating set up trial and error and minimizing planned downtime*

Built-in productivity

- Large selection of mark window options offers optimally matched applications for faster marking
- On-screen diagnostics track causes of downtime and help troubleshooting to get the line back up and running quickly*
- High speed capability allows marking at 150,000 products per hour

Code Assurance

- Optional CLARiTY® Laser Controller offers built-in software features that help reduce operator errors, to ensure products are coded correctly
- High quality, permanent codes help assure product traceability and tamper-proofing
- High resolution marking head delivers consistent, crisp codes

Simple usability

- Most flexible integration solution with 32 standard beam delivery options
- Quick set up and easy redeployment via detachable umbilical cable for easy routing on the line and simple-to-use accessory connections
- 5 interface options plus a choice of networking communications to match your preferred workflow

* With optional CLARiTY® Laser Controller

Videojet® 3340

Laser Marking System

Marking speed

Up to 2,000 characters/sec.⁽¹⁾

Line speed

Up to 15m/sec. (49ft/sec.)⁽¹⁾

Marking window

Approx. 30x38mm² to 601x400mm²

Wavelengths

10.6µm, 10.2µm and 9.3µm

Marking formats

Standard industrial fonts (Type 1 Windows® TrueType®) and Single line fonts
Machine readable codes (OCR, 2D-matrix, etc.)
Bar codes: BC25, BC251, BC39, BC128, GS1-128, EAN13, UPC_A, RSS14, RSS14 Truncated, RSS14 Stacked, RSS14 Stacked Omnidirectional, RSS Limited, RSS Expanded, etc.
Graphics, logos, symbols, etc.
Linear, circular, angular, reverse, rotate
Sequential and batch numbering
Automatic date, layer and time coding; real-time clock
Dot mode enables marking 2D codes faster than traditional grid mode

Laser tube

Sealed CO₂ laser, power class 30-Watt

Beam deflection

Steered beam with digital high-speed galvanometer scanners

Focusing

Focal lengths: 64/ 95/ 127/ 190/ 254 mm (2.5/ 3.75/ 5.0/ 7.5/ 10.0 inches);
63.5/ 85/ 100/ 150/ 200/ 300/ 351/ 400 mm (2.50/ 3.35/ 3.94/ 5.9/ 7.87/ 11.8/ 13.8/ 15.75 inches); 400/ 500/ 600 mm (15.75/ 19.68/ 23.62 inches)

Multiple operator interface options

Handheld controller
PC software
TCS Touch Control Software
CLARiTY® Laser Controller
Smart Graph Com

Language capabilities⁽²⁾

Arabic, Bulgarian, Czech, Danish, English, German, Greek, Finnish, French, Hebrew, Hungarian, Italian, Japanese, Korean, Dutch, Norwegian, Polish, Portuguese, Romanian, Russian, Serbian, Simplified Chinese, Slovak, Spanish, Swedish, Thai, Traditional Chinese, Turkish, Vietnamese; interface dependent

⁽¹⁾ Maximum marking and line speed is application dependent

⁽²⁾ With optional CLARiTY® Laser Controller

INVISIBLE LASER RADIATION

AVOID EYE OR SKIN EXPOSURE
TO DIRECT OR SCATTERED RADIATION

MAX. AVERAGE POWER: 45 W
WAVELENGTH: λ = 9-11 nm
LASER CLASS 4
(EN 60825-1:2014)

Communication

Ethernet, TCP/IP and RS232 optional
Inputs for encoders and product detector triggers
3 inputs/ 7 outputs for start/ stop signals, machine/ operator interlocks, alarm outputs;
with additional I/Os available
Customer-specific solutions available

Integration

Direct integration into complex production lines via scripting interface
Flexible beam delivery options (beam extension unit/ beam turning unit)
Detachable umbilical for simple integration; available in 3 lengths

Electrical requirements

100-240 VAC (autorange), ~50/60Hz, 1PH, 0.70KW

Cooling system

Air cooled

Environment

Temperature 40-105° F (5-40° C)
Humidity 10%-90%, non-condensing

Sealing and safety standards

Supply Unit: IP54, optional IP65
Marking Unit: IP54, optional IP65
Optional safety module provides Performance Level d (PFL-d) in accordance to EN 13849-1
IEC/EN 60825-1:2014


Approximate weight

Supply unit: IP54/IP65 25.4lbs. (11.5kg)
Marking unit: IP54 42.1lbs. (19.1kg); IP65 44.1lbs. (20kg)


Applicable certifications

CE, TÜV/NRTL, FCC
Compliance (no certification required): ROHS, CDRH/FDA

Marking unit dimensions - IP54 with SHC60 marking head



Supply cabinet dimensions - IP32



1-800-265-4783

info@crawfordpackaging.com

www.crawfordpackaging.com

 **Crawford
Packaging**

©2016 Videojet Technologies Inc. — All rights reserved.

Videojet Technologies Inc.'s policy is one of continued product improvement. We reserve the right to alter design and/or specifications without notice. Windows is a registered trademark of Microsoft Corporation. TrueType is a registered trademark of Apple Inc., registered in the United States and other countries.

Part No. SL000631
ss-3340-us-0616
Printed in U.S.A.

 **VIDEOJET®**